



PTFE0L - Teflon®

**NON-SHRINK, POLYTETRAFLUOROETHYLENE TUBING
LIGHT WALL (AWG Spaghetti sized tubing)**

Applications

PTFE0L is a light wall non-shrink, flame retardant polytetrafluoroethylene tube. It is designed for a wide range of applications requiring high heat-resistance.

Features

- ★ Continuous operating temperature: -75 °C to +260 °C (-103 °F to +500 °F)
- ★ Highly heat-resistant
- ★ High resistance to chemicals and oils

Standards

- ★ Declared Dimension Life (DDL) - 12 years
- ★ Meets V-0 Flammability
- ★ RoHS & REACH Compliant

Specification Values

Property		Test Method	Value
Physical	Specific Gravity (Max.)	ASTM D792	2.20
	Elongation (Min.)	ASTM D638	200%
	Tensile Strength (Min.)	ASTM D638	2500 psi
	Hardness Durometer	ASTM D2240	D-60
Electrical	Dielectric Strength	ASTM D149	1400 Volts/mil
	Volume Resistivity (Min.)	ASTM D257	$10^{18} \Omega \cdot \text{cm}$
General	Chemical/Solvent Resistance	-	Excellent
	Water Absorption (Max.)	ASTM D570	0.01
	Flammability Rating	UL 94	V-0

Rev. March 2024



Dunbar Products, LLC
Tubing and Identification Products



1302 Champion Circle, Carrollton, TX 75006
Tel: (469) 568-0800
Fax: (469) 568-0808



PTFE0L - Teflon®

NON-SHRINK, POLYTETRAFLUOROETHYLENE TUBING
LIGHT WALL (AWG Spaghetti sized tubing)



Product Dimensions

AWG Size	Inside Diameter					
	Internal Diameter in (D)		Internal Diameter mm (D)		Wall Thickness (Nominal) (t)	
	Min	Max	Min	Max	in	mm
32	.007	.011	.180	.280	.006 ± .002	.152 ± .051
30	.010	.015	.254	.381	.006 ± .002	.152 ± .051
28	.013	.018	.330	.480	.006 ± .002	.152 ± .051
26	.016	.021	.410	.560	.006 ± .002	.152 ± .051
24	.020	.026	.510	.670	.006 ± .002	.152 ± .051
23	.023	.029	.584	.740	.006 ± .002	.152 ± .051
22	.025	.032	.640	.810	.006 ± .002	.152 ± .051
21	.029	.035	.740	.890	.006 ± .002	.152 ± .051
20	.032	.040	.813	1.02	.006 ± .002	.152 ± .051
19	.036	.044	.914	1.12	.006 ± .002	.152 ± .051
18	.040	.049	1.02	1.25	.006 ± .002	.152 ± .051
17	.045	.054	1.14	1.37	.006 ± .002	.152 ± .051
16	.051	.061	1.30	1.55	.006 ± .002	.152 ± .051
15	.057	.067	1.45	1.70	.006 ± .002	.152 ± .051
14	.064	.074	1.63	1.88	.008 ± .002	.203 ± .051
13	.072	.082	1.83	2.08	.008 ± .002	.203 ± .051
12	.081	.091	2.06	2.31	.008 ± .002	.203 ± .051
11	.091	.101	2.31	2.57	.008 ± .002	.203 ± .051
10	.102	.112	2.59	2.85	.008 ± .002	.203 ± .051
9	.114	.124	2.90	3.15	.008 ± .002	.203 ± .051
8	.129	.141	3.28	3.58	.008 ± .002	.203 ± .051
7	.144	.158	3.66	4.01	.008 ± .002	.203 ± .051
6	.162	.178	4.11	4.52	.010 ± .003	.254 ± .076
5	.182	.198	4.62	5.03	.010 ± .003	.254 ± .076
4	.204	.224	5.18	5.69	.010 ± .003	.254 ± .076
3	.229	.249	5.82	6.33	.010 ± .003	.254 ± .076
2	.258	.278	6.55	7.06	.010 ± .003	.254 ± .076
1	.289	.311	7.34	7.90	.010 ± .003	.254 ± .076
0	.325	.347	8.26	8.81	.012 ± .003	.304 ± .076

Rev. March 2024



Dunbar Products, LLC
Tubing and Identification Products



1302 Champion Circle, Carrollton, TX 75006
Tel: (469) 568-0800
Fax: (469) 568-0808